



TRAKPACTOR 290

The Powerscreen Trakpactor 290 Impact Crusher is a versatile and easy to use machine that can operate in the most demanding of applications such as construction and demolition, asphalt, concrete, and natural rock. Its compact design allows it to operate in restricted spaces and ease of transportation makes it the ideal solution for rental and smaller contract jobs.

An optional SR section is fully detachable using quick release hydraulics and electrics.



✓ APPLICATIONS

AGGREGATE



Blasted rock
River rock

RECYCLING



C & D waste
Foundry waste

MINING



Processed ores
Processed minerals

www.powerscreen.com



TECHNICAL HIGHLIGHTS

INCREASED PRODUCTIVITY



- Highly aggressive chamber with 4 bar rotor / 2 aprons for high productivity.
- Start up motor for smooth engagement and increasing clutch life.
- Fully enclosed hopper to eliminate spillage
- Compact footprint allows machine to excel in smaller contract and/or rental jobs

VERSATILITY



- Converts to Trakpactor 290SR in minutes thanks to quick attach/detach SR section. Ideal for regions with transport weight restrictions.
- Recirculating conveyor slews hydraulically from recirculation to stockpiling mode.


SERVICEABILITY



- Excellent access features for serviceability eg. hydraulic cabinet at ground level; unrestricted access to both sides of power unit; steel pipes in key locations.



TECHNICAL SPECIFICATION



1 HOPPER

Length: 3.8m (12' 6")
Width: 2m (6' 7")
Capacity: 3.3m³ (4.3 cu. Yd.)

2 CRUSHER

Feed Opening: 1030mm x 790mm (41" x 31")
Min. CSS: 50mm (2") upper apron
Max. CSS: 150mm (6") upper apron

3 BYPASS CONVEYOR (OPTION)

Width: 500mm (20")
Discharge height: 2.48m (8' 2")

4 FEEDER

Vibrating grizzly feeder
Length: 3.8m (12' 6")
Screen Area: 1500mm x 950mm (5' x 3' 2")

5 TRACKS

Width: 400mm (1' 4")

6 POWER UNIT

Tier IIIA: Volvo D8 235kW (315hp)
Tier 4F: Volvo D8 235kW (315hp)
Stage V: Volvo D8 235kW (315hp)

7 TRAKPACTOR 290SR

All features of standard machine plus:
• 2.74m x 1.5m (9' x 5') post-screen, side tensioned mesh
• 1200mm (47") wide fines conveyor
• 500mm (20") wide cross conveyor
• 500mm (20") hydraulic folding recirc conveyor



DIMENSIONS

WORKING



12.6m (41' 5")

3.7m (12' 2")



5.22m (17' 1")

3.7m (12' 2")

TRANSPORT

Length: 9.97m (32' 9")
Width: 2.55m (8' 4")
Height: 3.16m (10' 5")

290SR

Length: 14.76m (48' 5")
Width: 2.9m (9' 6")
Height: 3.18m (10' 5")

WEIGHT

Standard: 28,700kg (63,273lbs)
290SR: 34,200kg (75,398lbs)

GET IN TOUCH

Dungannon
200 Coalisland Road, Dungannon,
Co Tyrone, BT71 4DR, Northern Ireland
Tel: +44 (0) 28 87 718 500
Fax: +44 (0) 28 87 747 231

Louisville
11001 Electron Drive,
Louisville, Kentucky, 40299 USA
Tel: +1 502 736 5200
Fax: +1 502 736 5202



www.powerscreen.com

The material in this document is for information only and is subject to change without notice. Powerscreen assumes no liability resulting from errors or omissions in this document, or from the use of the information contained herein. Due to continual product development we reserve the right to change specifications without notice. Product performance figures given in this brochure are for guidance purposes only, this information does not constitute an expressed or implied warranty or guarantee, but shows test examples provided by Dealers. These results will vary depending on crusher chamber settings, screen media and sizes, feed source and types of material being processed. Photographs are for illustrative purposes only, some or all of the machines in the illustrations may be fitted with optional extras. Please check with your Dealer for details on optional extras. All machines are CE Approved.

Powerscreen® is a registered trademark of Terex GB Limited in the United States of America and many other countries. Copyright 2024 Terex GB Limited. Published and Printed in November 2024.