



PREMIERTRAK 760

The Premiertrak 760 Jaw Crusher incorporates the Terex Jaques JW55 single toggle jaw, helping to maximise throughput capacity. This machine also features a vibrating pan feeder linked to an aggressive independent pre-screen, which provides essential removal of fines material before it reaches the chamber.

Please note: The Premiertrak 760 is available in Tier 3 engine regions only.



✓ APPLICATIONS

AGGREGATE



Sand & gravel
Blasted rock
River rock

RECYCLING



C & D waste
Overburden
Foundry waste

MINING



Processed ores
Processed minerals

www.powerscreen.com



TECHNICAL HIGHLIGHTS ✓

INCREASED PRODUCTIVITY

- Terex® Jaques jaw chamber with hydraulic CSS adjustment.
- 10m³ hopper capacity. Additional capacity available with the optional side extensions.



VERSATILITY

- Vibrating pan feeder linked to an aggressive independent pre-screen which provides essential removal of fines material before it reaches the chamber



SERVICEABILITY

- Excellent under crusher access for removal of wire with hydraulic raise lower product conveyor
- Easily accessed power unit canopy



ADDITIONAL OPTIONS

- Optional bypass conveyor available or material can run under the jaw to the product conveyor.
- Single and twin pole magnets available.





TECHNICAL SPECIFICATION



1 HOPPER

Wear resistant feed hopper
Length: 4.67m (15' 5")
Width: 2.86m (9' 5")
Capacity: 10m³ (13 cu. yd.)

2 CRUSHER

Terex JW55 chamber - Single Toggle Jaw
Chamber size: 1415mm x 820mm (55" x 32")
Min CSS: 75mm (3")*
Max CSS: 225mm (9")*

3 PRODUCT CONVEYOR

Width: 1400mm (55")
Discharge height: 4.5m (14' 9")

4 BYPASS CONVEYOR (OPTION)

Width: 750mm (30")
Discharge height: 3.7m (12' 5")

5 TRACKS

Width: 500mm (1' 8")

6 POWER UNIT

Tier 3 Equivalent: CAT C13328kW (440hp)
Tier 4F / Stage V: Scania DC13 84A 331kW (444hp)
Fuel Tank Capacity: 750 L (198 US G)



DIMENSIONS

Working



6.38m (21' 1")
with bypass conveyor

Transport

Length: 18.1m (59' 4")
Width: 3.3m (10' 10")
Height: 3.86m (12' 8")

Weight

83,450kg (183,976lbs)
- with bypass conveyor and twin pole magnet

GET IN TOUCH

Dungannon
200 Coalisland Road, Dungannon,
Co Tyrone, BT71 4DR, Northern
Ireland
Tel: +44 (0) 28 87 718 500
Fax: +44 (0) 28 87 747 231

Louisville
11001 Electron Drive,
Louisville, Kentucky, 40299
USA
Tel: +1 502 736 5200
Fax: +1 502 736 5202



www.powerscreen.com

The material in this document is for information only and is subject to change without notice. Powerscreen assumes no liability resulting from errors or omissions in this document, or from the use of the information contained herein. Due to continual product development we reserve the right to change specifications without notice. Product performance figures given in this brochure are for guidance purposes only, this information does not constitute an expressed or implied warranty or guarantee, but shows test examples provided by Dealers. These results will vary depending on crusher chamber settings, screen media and sizes, feed source and types of material being processed. Photographs are for illustrative purposes only, some or all of the machines in the illustrations may be fitted with optional extras. Please check with your Dealer for details on optional extras. All machines are CE Approved.

Powerscreen® is a registered trademark of Terex GB Limited in the United States of America and many other countries. Copyright 2025 Terex GB Limited. Published and Printed in 2025.