



1300X MAXTRAK

The Powerscreen® 1300X Maxtrak is a medium to large sized track mobile cone crusher, ideally suited to secondary applications such as taking an all in feed from a primary crusher. With the high performance and proven Terex cone, this plant excels in the production of sub-base or aggregates, providing excellent throughput & reduction ratios.



✓ APPLICATIONS

AGGREGATE



Sand & gravel
Blasted rock
River rock

RECYCLING



C&D waste
Overburden
Foundry waste

MINING




Processed ores
Processed minerals



TECHNICAL HIGHLIGHTS


EXCEPTIONAL PERFORMANCE

- Proven TC1300X Terex Cone has been tried, tested and proven all over the world.
- Renowned Automax® crusher technology.
- Economical to operate with a highly fuel efficient direct drive system.
- Cone feed box level control to maintain choke feeding.



VERSATILITY

- Ideal for C&D waste / recycling applications with hydraulic deflector plate and hydraulically raise / lower product conveyor options.
- Pre-screen option to maximise production through the cone by removing as much fine material as possible before it enters the cone chamber.



SERVICEABILITY

- Centralised low level hydraulics and electrics.





TECHNICAL SPECIFICATION



1 HOPPER

Fixed feed hopper
Feed height: 3.07m (10' 11")
Hopper width: 2.25m (7' 5")
Capacity: 6m³ (7.8 cu. yd.)

2 CRUSHER

TC1300X Terex Crusher
2 operating modes available

3 PRODUCT CONVEYOR

Width: 1100mm (44")
Discharge height: 3.6m (11' 10")

4 FEED CONVEYOR

Width: 1300mm (52")
Drive: Hydraulic variable speed drive via gearbox

5 TRACKS

Width: 500mm (1' 8")

6 POWER UNIT

Tier 3 Equivalent: CAT C15
403 kW (540hp)

Tier 4F / Stage V: Scania DC13,
405 kW (550hp)

Fuel tank capacity: 1000L
(264 US Gal)




DIMENSIONS



TRANSPORT DIMENSIONS

Length: 17.92m (58' 10")
Height: 3.8m (12' 6")
Width: 3.0m (9' 10")
Weight: 51,500kg (113,538lbs)



GET IN TOUCH

Dungannon
200 Coalisland Road, Dungannon,
Co Tyrone, BT71 4DR, Northern Ireland
Tel: +44 (0) 28 87 718 500
Fax: +44 (0) 28 87 747 231

Louisville
11001 Electron Drive,
Louisville, Kentucky, 40299 USA
Tel: +1 502 736 5200
Fax: +1 502 736 5202

Hosur
E-18, Phase II, Sipcot Expansion II,
Moranapalli, Hosur,
Tamil Nadu 635109, India



www.powerscreen.com

The material in this document is for information only and is subject to change without notice. Powerscreen assumes no liability resulting from errors or omissions in this document, or from the use of the information contained herein. Due to continual product development we reserve the right to change specifications without notice. Product performance figures given in this brochure are for guidance purposes only, this information does not constitute an expressed or implied warranty or guarantee, but shows test examples provided by Dealers. These results will vary depending on crusher chamber settings, screen media and sizes, feed source and types of material being processed. Photographs are for illustrative purposes only, some or all of the machines in the illustrations may be fitted with optional extras. Please check with your Dealer for details on optional extras. All machines are CE Approved.

Powerscreen® is a registered trademark of Terex GB Limited in the United States of America and many other countries. Copyright 2024 Terex GB Limited. Published and Printed in 2024