



CHIEFTAIN 1400

The legendary Powerscreen® Chieftain 1400 incline screen is one of Powerscreen's most popular screening products and is ideally suited for small to medium sized operators and contractors who require a versatile machine capable of operating in a number of applications such as sand and gravel, aggregates and recycling. User benefits include hydraulic folding conveyors for a quick set-up time, screen walkways and access ladders for ease of maintenance, and a drop down tail conveyor to aid screen media changes.



✓ APPLICATIONS

AGGREGATE



Sand & gravel
Blasted rock
River rock

RECYCLING



Top soil
C&D waste
Composted materials
Wood by-products

MINING



Processed ores
Processed minerals

www.powerscreen.com



TECHNICAL HIGHLIGHTS ✓

INCREASED PRODUCTIVITY


- High capacity throughput producing up to 400tph (441 US tph) depending on application
- Heavy duty single shaft incline screenbox with adjustable angle
- Its compact size and rapid set up times means quicker to get working on site and increased uptime
- Engine protection shutdown system

VERSATILITY

- Maximum mobility with heavy duty, low ground pressure crawler tracks.
- Engine protection shutdown system

SERVICEABILITY

- Power unit featuring a transverse engine arrangement to aid access & serviceability
- Fines conveyor has hydraulic folding head section along with hydraulic raise/lower
- Excellent service access to powerunit with simple, easy to use controls





TECHNICAL SPECIFICATION



1 HOPPER

Hopper Capacity (with grid): 6.7m³
(8.75 cu. yd.)
Adjustable angle tipping grid

2 MAIN CONVEYOR

Width: 1050mm (42")

3 TAIL CONVEYOR (FINESIZE)

Width: 1200mm (48")
Discharge height: 3.93m (12' 11")

4 SIDE CONVEYOR (MIDSIZE & OVERSIZE)

Width: 650mm (26")
Discharge height: 4.72m (15' 6")
Individual variable speed

5 SCREENBOX

4 Bearing, 2 deck screenbox
Size: 3.33m x 1.53m (11' x 5')
Highly aggressive screen drive

6 TRACKS

Width: 500mm (1' 8")

7 POWER UNIT

Engine Tier 3 Equivalent:
CAT C4.4 83 kW (111.3hp)
Engine Tier 4 / Stage IV:
CAT C3.6 82 kW (110hp)
Engine Stage V: JCB 4.8 81 kW (109hp)

8 FEEDER CONVEYOR

Width: 1050mm (42")
Variable speed



DIMENSIONS



Transport

Length: 15.5m (51')
Width: 3m (9' 10")
Height: 3.4m (11' 2")

Weight

24,970kg (55,049lbs)

GET IN TOUCH

Dungannon

200 Coalisland Road, Dungannon,
Co Tyrone, BT71 4DR, Northern Ireland
Tel: +44 (0) 28 87 718 500
Fax: +44 (0) 28 87 747 231

Louisville

11001 Electron Drive,
Louisville, Kentucky, 40299 USA
Tel: +1 502 736 5200
Fax: +1 502 736 5202



www.powerscreen.com

The material in this document is for information only and is subject to change without notice. Powerscreen assumes no liability resulting from errors or omissions in this document, or from the use of the information contained herein. Due to continual product development we reserve the right to change specifications without notice. Product performance figures given in this brochure are for guidance purposes only, this information does not constitute an expressed or implied warranty or guarantee, but shows test examples provided by Dealers. These results will vary depending on crusher chamber settings, screen media and sizes, feed source and types of material being processed. Photographs are for illustrative purposes only, some or all of the machines in the illustrations may be fitted with optional extras. Please check with your Dealer for details on optional extras. All machines are CE Approved.

Powerscreen® is a registered trademark of Terex GB Limited in the United States of America and many other countries. Copyright 2024 Terex GB Limited. Published and Printed in 2024.