




WARRIOR 800

The Powerscreen® Warrior 800 has been specifically designed for those for whom versatility and transportability are of key importance. The machine is a multi-purpose heavy duty incline two deck screen, capable of stockpiling, 3 way splitting or scalping before and after crushing units. Its highly aggressive screen can accept bofor bars, finger screens, woven mesh and punch plates.

User benefits include a rapid set-up time and ease of operation aided by hydraulic folding tail and side conveyors, rigid feed hopper sides and two speed tracks. Simplified slide out tail conveyor facilities aid media access and screen media changes.



✓ APPLICATIONS

AGGREGATE



Sand & gravel
Blasted rock
River rock

RECYCLING




Top soil
C&D waste
Composted materials

MINING



Processed ores
Processed minerals



TECHNICAL HIGHLIGHTS ✓

INCREASED PRODUCTIVITY




- Heavy duty incline screenbox with adjustable stroke & speed
- Maximum mobility with heavy duty, low ground pressure tracks
- High performance hydraulic system - cast iron pumps & motors complete with hydraulic cooler
- Variable speed hopper featuring impact bars & rollers

VERSATILITY

- Versatile unit for 3 way splitting, stockpiling or scalping before or after a crusher

SERVICEABILITY

- Power unit featuring a transverse engine arrangement to aid access & serviceability
- Hydraulic slide out facility on tail conveyor, excellent bottom deck access
- Simple to operate & maintain





TECHNICAL SPECIFICATION



1 HOPPER

Capacity: 2.9m³ (3.8 yds³)

2 FEED CONVEYOR

Width: 1050mm (42")
Heavy duty belt feeder
Super grip drive drum

3 SCREENBOX

2 Bearing, 2 deck screenbox
Size: 2.77m x 1.22m (9' x 4')

4 SIDE CONVEYOR (MIDSIZE)

Width: 650mm (26") wide
Discharge height: 3.64m (11'11")
Variable speed control

5 TAIL CONVEYOR (OVERSIZE)

Width: 1050mm (42")
Discharge height: 3.03m (9'11")
Hydraulic combined slide out & fold mechanism
Variable speed control

6 TRACKS

Width: 400mm (1' 4")

7 POWER UNIT


Tier 3 Equivalent: Cat C4.4 62kW (83hp)
Tier 4F: Cat C2.2 55 kW (74hp)
Stage V: Kohler 2.5 55 kW (74hp)

8 SIDE CONVEYOR (FINESIZE)

Width: 650mm (26")
Discharge height: 3.82m (12'7")



DIMENSIONS



Transport

Length: 9.23m (30' 3")
Width: 2.5m (8' 2")
Height: 3.09m (10' 1")

Weight

16,700kg (36,817lbs)

GET IN TOUCH

Dungannon

200 Coalisland Road, Dungannon,
Co Tyrone, BT71 4DR, Northern Ireland
Tel: +44 (0) 28 87 718 500
Fax: +44 (0) 28 87 747 231

Louisville

11001 Electron Drive,
Louisville, Kentucky, 40299 USA
Tel: +1 502 736 5200
Fax: +1 502 736 5202



www.powerscreen.com

The material in this document is for information only and is subject to change without notice. Powerscreen assumes no liability resulting from errors or omissions in this document, or from the use of the information contained herein. Due to continual product development we reserve the right to change specifications without notice. Product performance figures given in this brochure are for guidance purposes only, this information does not constitute an expressed or implied warranty or guarantee, but shows test examples provided by Dealers. These results will vary depending on crusher chamber settings, screen media and sizes, feed source and types of material being processed. Photographs are for illustrative purposes only, some or all of the machines in the illustrations may be fitted with optional extras. Please check with your Dealer for details on optional extras. All machines are CE Approved.

Powerscreen® is a registered trademark of Terex GB Limited in the United States of America and many other countries. Copyright 2024 Terex GB Limited. Published and Printed in January 2024.